according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Kühlflüssigkeit HKF 15.1 MW 65

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coolant

Industrial uses

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: Conzelmann Schweißhandelsgesellschaft mbH

Street: Siemensstrasse 9 Place: D-89331 Burgau

Telephone: +49 (0) 8222 413880 Telefax: +49 (0) 8222 41388-20

e-mail: office@conzelmann-gmbh.de

Contact person: main office Telephone: +49 (0) 8222 41388-0

e-mail: office@conzelmann-gmbh.de

1.4. Emergency telephone +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements: Harmful if swallowed. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

There is no ingredient on the SVHC list

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

ethanediol, ethylene glycol

Signal word: Warning

Pictograms:





Hazard statements

H302 Harmful if swallowed.
H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 2 of 11

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No other hazards are known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Ingredient:

ethanediol, ethylene glycol propan-1-ol; n-propanol,

Water, Inhibitor

Hazardous components

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	GHS Classification					
107-21-1	ethanediol, ethylene glyd	col		25 - <30 %		
	203-473-3	603-027-00-1	01-2119456816-28			
	Acute Tox. 4, STOT RE 2					
71-23-8	propan-1-ol; n-propanol			1 - <5 %		
	200-746-9	603-003-00-0	01-2119486761-29			
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing.

If unconscious place in recovery position and seek medical advice.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Remove contaminated, saturated clothing immediately.

After contact with eves

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain

according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 3 of 11

immediate medical attention. Let water be drunken in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder, alcohol resistant foam, Carbon dioxide (CO2), Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. Full protection suit

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

Avoid contact with eyes and skin.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Shafts and sewers must be protected from entry of the product.

6.3. Methods and material for containment and cleaning up

Provide fresh air.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8.

Wear personal protection equipment (refer to section 8).

Do not breathe gas/vapour/aerosol.

Keep container tightly closed.

In case of inadequate ventilation wear respiratory protection.

Avoid contact with eyes and skin.

according to Regulation (EC) No 1907/2006_2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 4 of 11

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Further information on handling

Use only in well-ventilated areas.

When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep/Store only in original container.

Keep away from heat.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from: Frost, Heat, Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
107-21-1	ethanediol, ethylene glycol				
Worker DNEL,	long-term	inhalation	local	35 mg/m³	
Worker DNEL,	long-term	dermal	systemic	106 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	local	7 mg/m³	
Consumer DNE	EL, long-term	dermal	systemic	53 mg/kg bw/day	
,					
71-23-8	propan-1-ol; n-propanol				
Worker DNEL,	long-term	inhalation	systemic	268 mg/m³	
Worker DNEL,	acute	inhalation	systemic	1723 mg/m³	
Worker DNEL, long-term		dermal	systemic	136 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	80 mg/m³	
Consumer DNEL, acute		inhalation	systemic	1036 mg/m³	
Consumer DNEL, long-term		dermal	systemic	81 mg/kg bw/day	
Consumer DNE	EL, long-term	oral	systemic	61 mg/kg bw/day	

according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 5 of 11

PNEC values

CAS No	Substance				
Environmen	tal compartment	Value			
107-21-1	ethanediol, ethylene glycol				
Freshwater		10 mg/l			
Freshwater	(intermittent releases)	10 mg/l			
Marine wate	r	1 mg/l			
Freshwater	sediment	37 mg/kg			
Marine sedir	nent	3,7 mg/kg			
Micro-organ	sms in sewage treatment plants (STP)	199,5 mg/l			
Soil		1,53 mg/kg			
71-23-8	propan-1-ol; n-propanol				
Freshwater		10 mg/l			
Freshwater (intermittent releases)		10 mg/l			
Marine wate	r	1 mg/l			
Freshwater	sediment	22,8 mg/kg			
Marine sedir	nent	2,28 mg/kg			
Micro-organ	sms in sewage treatment plants (STP)	96 mg/l			
Soil		2,2 mg/kg			

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Ground and bond container and receiving equipment.

Carry out filling operations only at stations with exhaust ventilation facilities.

Make available sufficient washing facilities

Provide eye shower and label its location conspicuously

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection.

Only wear fitting, comfortable and clean protective clothing.

Avoid contact with skin, eyes and clothes.

Wash hands before breaks and after work.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink, smoke, sniff.

Eye/face protection

Eye glasses with side protection,

goggles

Hand protection

Tested protective gloves must be worn: DIN EN 374

NBR (Nitrile rubber) NR (natural rubber, natural latex) Butyl caoutchouc (butyl rubber)

Thickness of the glove material >= 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer. Wear cotton undermitten if possible.

Skin protection

Use protective clothing chemically resistant to this material.

according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 6 of 11

Wear anti-static footwear and clothing

Street clothing should be stored separately from work clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

suitable: Full-/half-/guarter-face masks (DIN EN 136/140) ABEK-P3

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Alcohol

pH-Value: 9,0-10,5

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

Softening point:

Pour point:

Solidifying point:

Telash point:

not determined not determin

Flammability

Solid: No information available.

Gas: No information available.

Explosive properties

not explosive.

Lower explosion limits:

Upper explosion limits:

No information available.

No information available.

No information available.

Auto-ignition temperature

Solid: No information available.
Gas: No information available.
Decomposition temperature: No information available.

Oxidizing properties

No information available.

Vapour pressure: not determined

Density: 1,038 g/cm³

Water solubility: completely miscible

Solubility in other solvents

No information available.

Partition coefficient:

Viscosity / dynamic:

No information available.

not determined

Vapour density:

No information available.

according to Regulation (EC) No 1907/2006_2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 7 of 11

Evaporation rate: No information available. Solvent separation test: No information available.

9.2. Other information

Solid content: not determined

freezing point: \sim -14 °C protection against cold: \sim -15 °C Conductivity: 20-35 μ S/cm

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: Oxidising agent, strong

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon dioxide, Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1814,9 mg/kg

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
107-21-1	ethanediol, ethylene glyco	ol				
	oral	LD50 mg/kg	7712	Rat	Study report (1968)	according to BASF-internal standards
	dermal	LD50 mg/kg	> 3500	Mouse	Fundamental and Applied Toxicology 27: 1	LD50 derived from developmental toxicity
71-23-8	propan-1-ol; n-propanol					•
	oral	LD50 mg/kg	ca. 8000	Rat	Study report (1975)	OECD Guideline 401
	dermal	LD50 mg/kg	4032	Rabbit	Arch. ind. hyg. occupat. med. 10, 61-68.	OECD Guideline 402

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006_2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 8 of 11

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol, ethylene glycol)

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested. Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
107-21-1	ethanediol, ethylene glyco	ol						
	Acute fish toxicity	LC50 mg/l	> 72860	96 h	Pimephales promelas	Environ. Toxicology and Chemistry, Vol.	EPA 600/4-90/027. U.S. Environmental Pro	
	Acute algae toxicity	ErC50 13000 mg/l	6500 -	96 h	Pseudokirchneriella subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	15380	7 d	Pimephales promelas	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen	
	Algea toxicity	NOEC mg/l	> 100	8 d	Scenedesmus quadricauda	REACh Registration Dossier	OECD Guideline 201	
	Crustacea toxicity	NOEC 15000 mg/l	7500 -	21 d	Daphnia magna	REACh Registration Dossier	other: ASTM	
71-23-8	propan-1-ol; n-propanol							
	Acute fish toxicity	LC50 mg/l	4555	96 h	Pimephales promelas	Vol. 1, pp 3, 5-16, 65-68. Center for La	OECD Guideline 203	
	Acute crustacea toxicity	EC50 mg/l	3644	48 h	Daphnia magna	Water Res 23: 495-499 (1989)	other: DIN 38412 Part 11, Daphnia- Short	
	Crustacea toxicity	NOEC mg/l	> 100	21 d	Daphnia magna	Study report (1997)	OECD Guideline 211	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

according to Regulation (EC) No 1907/2006_2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 9 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	ethanediol, ethylene glycol	-1,36
71-23-8	propan-1-ol; n-propanol	1,6

BCF

CAS No	Chemical name	BCF	Species	Source
71-23-8	propan-1-ol; n-propanol	0,88		Unpublished calculat

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Avoid release into the environment. slightly hazardous to water (WGK 1)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.

Print date: 23.06.2022

according to Regulation (EC) No 1907/2006 2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 10 of 11

14.3. Transport hazard class(es):
 14.4. Packing group:
 No dangerous good in sense of this transport regulation.
 No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: ethanediol, ethylene glycol; propan-1-ol; n-propanol

Information according to 2012/18/EU

Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

ethanediol, ethylene glycol propan-1-ol; n-propanol

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID:Règlement international conernat le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Refulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effectice concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Print date: 23.06.2022

according to Regulation (EC) No 1907/2006_2015/830

Kühlflüssigkeit HKF 15.1 MW 65

Revision date: 01.02.2022 Page 11 of 11

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method

R

Odiodidani modiod		
Calculation method		
Relevant H and EUH statements (number and full text)		
flammable liquid and vapour.		
H302 Harmful if swallowed.		

H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Print date: 23.06.2022